

Data Sheet

HD110T Digital Multimeter



Completely sealed, environment proof, professional digital multimeter

The HD Series of DMMs is designed for professional use in harsh environments. The meters are unusually rugged and reliable in everyday heavy use applications. Each meter is made using waterproof construction to prevent dirt, grime and moisture from entering the case and causing inaccurate readings or damaging shorts.

They are built of tough, fire-retardant thermoplastic resistant to grease and chemical spills, with all sensitive components shock-mounted for a drop resistant to at least eight feet.

Every meter in the HD line has an extended voltage measurement capability of 1500 V dc and 1000 V ac, unmatched by any other line of digital multimeters. The extended voltage ranges can withstand transients up to 3 kV.

The HD110T features:

- Temperature measurement to 1093 °C (2000 °F)
- V dc accuracy of 0.1 %
- Superior 1200-hour battery life
- Shock and vibration: Meets MIL-T-28800
- Low battery indicator at 100 hours
- Type K probe included

Specifications (at 23 °C ± 5 °C, < 70 % R.H.)

Function	Range	Accuracy
Voltage		
DC Voltage	200 mV, 2 V, 20 V, 200 V, 1500 V	± (0.1 % rdg + 1 dgt)
NMRR	> 60 db (> 49 Hz)	
CMRR	> 60 db (> 49 Hz)	
AC Voltage	200 mV, 2 V, 20 V (45 Hz to 2 kHz) 200 mV, 2 V, 20 V (2 kHz to 5 kHz) 200 V (45 Hz to 1 kHz) 1000 V (45 Hz to 500 Hz) 1000 V (500 Hz to 1000 Hz)	± (0.75 % rdg + 3 dgts) ± (1.5 % rdg + 5 dgts) ± (0.75 % rdg + 3 dgts) ± (0.75 % rdg + 3 dgts) ± (1.5 % rdg + 5 dgts)
AC Conversion	Average sensing, rms indicating	
Resolution	0.1 mV in 200 mV range	
Input Impedance	10 MΩ (dc) 10 MΩ//75 pF (ac)	
Current		
DC Current	2 A 10 A	± (0.35 % rdg + 1 dgt) ± (1.0 % rdg + 1 dgt)
AC Current	200 μA, 2 mA, 20 mA, 200 mA, 2 A (45 Hz to 2 kHz) 10 A (45 Hz to 400 Hz)	± (0.9 % rdg + 3 dgts) ± (1.5 % rdg + 3 dgts)
AC Conversion Type	Average sensing, rms indicating	
Resolution	0.1 μA in 200 μA range	
Voltage Burden	200 μA range: 1 mV/μA 2 mA range: 100 mV/1 mA 20 mA range: 10 mV/1 mA 200 mA range: 1.2 mV/1 mA 2 A range: 300 mV/1 A 10 A range: 37 mV/1 A	
Resistance	200 Ω, 2 kΩ, 20 kΩ, 200 kΩ, 2 MΩ 20 MΩ	± (0.2 % rdg + 1 dgt) ± (1.0 % rdg + 1 dgt)
Resolution	0.1 Ω in 200 Ω range	
Max Open Circuit Voltage	300 mV	
Max In-Range Voltage	200 mV	
Max Test Current	2.5 mA	

Specifications (at 23 °C ± 5 °C, < 70 % R.H.) *cont.*

Function	Range	Accuracy
Temperature	- 4 °F to 31 °F	± 6 °F
	32 °F to 572 °F	± 5 °F
	573 °F to 800 °F	± (1 % rdg + 2 °F)
	801 °F to 1000 °F	± (2 % rdg + 3 °F)
	1001 °F to 1999 °F	± 3 % rdg
Resolution	1 °F	
Thermocouple Type	Type K	± 3.6 °F
Diode Test	0 to 2 V	± (6.0 % rdg + 2 dgts)
Test Current	2 mA ± 20 %	
Display Response	1 sec.	
Continuity		
Tone and Visual Signal	< 80 Ω	
Overload Protection		
Transient Protection		
ACV/DCV any Range	3 kV for 10 μs	
DCV Range	1500 V dc or pk ac any range	
ACV Ranges	1000 Vrms/1500 V pk ac or 250 V dc (5 sec max. above 450 V rms on 200 mV range)	
Current Range	200 μA to 2 A ranges: 2 A/600 V fuse (3000 A interrupt rating) 10 A range: 15 A/600 V fuse (100 kA interrupt rating)	
Resistance/Diode/Continuity Ranges	600 V dc or rms ac	

General Specifications

Display	3-1/2 digit LCD
Measurement Rate	2.5/sec.
Response Time	< 2 msec
Battery Type	One 9 V battery NEDA 1604
Battery Life	1200 hours
Operating Temperature	0 °C to 50 °C (32 °F to 122 °F)/0 to 80 % R.H.
Storage Temperature	-40 °C to 65 °C (-40 °F to 149 °F)
Dimensions (HxWxD)	184 mm x 102 mm x 50 mm (6.9 in x 3.9 in x 2.0 in)
Weight	543 g (1 lb, 3 oz)
Warranty	One-year

No waiting.

No shipping
charges.

No hassle warranty

Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that a Meterman test tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.


Included Accessories

Type K bead probe (TP255), test leads (TL245), battery and users manual.

Optional Accessories

VC221A Vinyl Case
DL243C Basic Test Lead Kit
DL248C Deluxe Test Lead Kit
TL36 Test Lead Set with Alligator Clips
DC205B Deluxe Hard Carrying Case

Meterman®
The right tool, everyday.™

Meterman Test Tools

website: www.metermantesttools.com
 email: info@metermantesttools.com

6920 Seaway Blvd.
 Everett, WA 98203
 fax: 425-446-4882
 tel: 877-596-2680

Meterman Test Tools Europe
 P.O. Box 1186
 5602 BD Eindhoven
 The Netherlands

©2005 Meterman Test Tools. All rights reserved.
 8/2005 1646306 D-US-N Rev B